

Rolo de leva com eixo CFES12-UUR-IKO - CFES12-UUR-IKO

<https://www.123rolamento.pt/rolamento-manca/rolamento-esferas/rolo-leva-eixo/cfes12-uur-iko>

IKO
CAM FOLLOWERS
Solid Eccentric Stud Type Cam Followers **With Cage/With Screwdriver Slot**

Stud dia. mm	Identification number						Mass (Ref.)		
	Shield type		Sealed type		g	D	C	d ₁	
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
12			CFES 12	UUR	95	30	14	12	

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N-m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N	
G	G ₁	B _{max}	B _{1max}	B ₂	B ₃	C ₁	B ₁	B ₂	ε _{max}						
M12×1.5	13	15.2	40.2	25	6	0.6	6	3	0.6	0.4	21	21.9	7 910	9 790	9 790

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
N° Ean13	3616060459237
Diâmetro interior	12 mm
Diâmetro interior	0.472" inch
Diâmetro exterior	30 mm
Diâmetro exterior	1.181" inch
Espessura	14 mm
Espessura	0.551" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE