


Rolo de leva com eixo CFES12-1-UUR-IKO - CFES12-1-UUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfes12-1-uur-iko>

IKO

CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number						Mass (Ref.)		
	Shield type		Sealed type		g	D	C	d ₁	
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
12					105	32	14	12	

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	G ₁	B	B ₁	B ₂	B ₃	C ₁	B ₁	B ₂	B ₃						
M12×1.5	13	15.2	40.2	25	6	0.6	6	3	0.6	0.4	21	21.9	7 910	9 790	9 790

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060459275
Diâmetro interior	12 mm
Diâmetro exterior	32 mm
Espessura	14 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE