


Rolo de leva com eixo CFES16-UU-IKO - CFES16-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfes16-uu-iko>

IKO

CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers With Cage/With Screwdriver Slot



CFES16-UU

Stud dia. mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d ₁
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
16				CFES 16 UU	170	35	18	16

Boundary dimensions mm										Eccentricity E	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	G ₁	B	B ₁ max	B ₂	B ₃	C ₁	B ₁	B ₂	α ₂						
M16×1.5	17	19.6	52.1	32.5	8	0.8	6	3	0.6	0.5	26	58.5	12 000	18 300	18 300

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060459312
Diâmetro interior	16 mm
Diâmetro exterior	35 mm
Espessura	18 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE