

Rolo de leva com eixo CFE12-UU-IKO - CFE12-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe12-uu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number								Mass (Ref.)				
	Shield type				Sealed type				Ø	D	C	d ₂	
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 12	UU	105	30					14
16													

Boundary dimensions mm										Mounting dimension f Min, mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B max	B ₁ max	B ₂	C ₁	G ₁	G ₁ (1)	g	e					
M12×1.5	11.5	15.2	40.2	25	0.6	6	13.5	0.6	0.8	21	21.9	7 910	9 790	9 790

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060459916
Diâmetro interior	16 mm
Diâmetro exterior	30 mm
Espessura	14 mm
Peso	105 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE