


Rolo de leva com eixo CFE12-1-UUR-IKO - CFE12-1-UUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe12-1-uur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		\emptyset	D	C	d_2						
16	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	115	32	14	16						
CFE 12-1 UUR														
Boundary dimensions mm														
G	B_3	B_{max}	B_{min}	B_2	C_1	G_1	$(\theta)_{max}$	Mounting dimension f Min, mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C_0 N	Maximum allowable static load N		
M 8x1.25	9.5	12.2	32.2	20	0.6	*4	10.5	0.3	0.4	13	6.5	4 250	4 740	4 620

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060459947
Diâmetro interior	16 mm
Diâmetro interior	0.63" inch
Diâmetro exterior	32 mm
Diâmetro exterior	1.26" inch
Espessura	14 mm
Espessura	0.551" inch
Peso	115 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE