

Rolo de leva com eixo CFE18-UU-IKO - CFE18-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe18-uu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		M	D	C	d ₂						
24	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					CFE 18 UU	280	40	20	24	
Boundary dimensions mm														
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	g ₁	G ₁	(1) Fits	Mounting dimension f Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M18×1.5	17.5	21.6	58.1	36.5	0.8	6	19	1	0.8	29	86.2	14 800	25 200	25 200

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060460028
Diâmetro interior	24 mm
Diâmetro exterior	40 mm
Espessura	20 mm
Peso	280 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE