

Rolo de leva com eixo CFE20-1-UUR-IKO - CFE20-1-UUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe20-1-uur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		\emptyset	D	C	d_2
27	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	425	47	24	27
CFE 20-1 UUR								

Boundary dimensions mm										Eccentricity e	Mounting dimension f mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C_0 N	Maximum allowable static load N
G	B_3	B max	B_1 max	B_2	C_1	G_1	r_{max}	r_1	r_2						
M20 X 1.5	19.5	25.6	66.1	40.5	0.8	8	21	1	0.8	34	119	20 700	34 600	34 600	

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060460097
Diâmetro interior	27 mm
Diâmetro interior	1.063" inch
Diâmetro exterior	47 mm
Diâmetro exterior	1.85" inch
Espessura	24 mm
Espessura	0.945" inch
Peso	425 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE