

Rolo de leva com eixo CFE24-UU-IKO - CFE24-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe24-uu-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		ϕ	D	C	d_2						
33	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 24 UU	895	62	29	33					
Boundary dimensions mm														
G	B ₃	B _{max}	B _{1 max}	B ₂	C ₁	g ₁	G ₁	(¹) Eccentricity e	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	30 500	52 600	52 000

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060460134
Diâmetro interior	33 mm
Diâmetro exterior	62 mm
Espessura	29 mm
Peso	895 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE