

## Rolo de leva com eixo CFE24-1-UU-IKO - CFE24-1-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe24-1-uu-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		$\emptyset$	D	C	$d_2$						
33	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 24-1 UU	1 220	72	29	33					
Boundary dimensions mm														
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>1 max</sub>	B <sub>2</sub>	C <sub>1</sub>	g <sub>1</sub>	G <sub>1</sub>	(1) $\frac{f}{mm}$	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N	
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	30 500	52 600	52 000

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952816524
Diâmetro interior	33 mm
Diâmetro exterior	72 mm
Espessura	29 mm
Peso	1220 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE