

Rolo de leva com eixo CFE10-1-VBUU-IKO - CFE10-1-VBUU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe10-1-vbuu-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)																			
	Shield type		Sealed type		g	D	C	d _e																
13	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 10-1 VBUU	66	26	12	13															
Boundary dimensions mm																								
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	H	f	C	C ₀	N														
M10 × 1.25	10.5	13.2	36.2	23	0.6	—	12.5	4	0.3	0.4														
<table border="1"> <thead> <tr> <th>Mounting dimension</th> <th>Maximum splining torque</th> <th>Basic dynamic load rating</th> <th>Basic static load rating</th> <th>Maximum allowable static load</th> </tr> <tr> <th>f</th> <th>N·m</th> <th>C</th> <th>C₀</th> <th>N</th> </tr> </thead> <tbody> <tr> <td>16</td> <td>13.8</td> <td>9 570</td> <td>14 500</td> <td>8 650</td> </tr> </tbody> </table>										Mounting dimension	Maximum splining torque	Basic dynamic load rating	Basic static load rating	Maximum allowable static load	f	N·m	C	C ₀	N	16	13.8	9 570	14 500	8 650
Mounting dimension	Maximum splining torque	Basic dynamic load rating	Basic static load rating	Maximum allowable static load																				
f	N·m	C	C ₀	N																				
16	13.8	9 570	14 500	8 650																				

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060460448
Diâmetro interior	13 mm
Diâmetro interior	0.512" inch
Diâmetro exterior	26 mm
Diâmetro exterior	1.024" inch
Espessura	12 mm
Espessura	0.472" inch
Peso	66 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE