

Rolo de leva com eixo CFE12-VBUUR-IKO - CFE12-VBUUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe12-vbuur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole

Outside diameter of eccentric roller mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
16	CFE 12 VBUUR						107	30	14	16

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	H	Excentricity e	Flank angle (°)	Flank radius R						
M12×1.5	11.5	15.2	40.2	25	0.6	6	13.5	6	0.6	0.8	21	21.9	13 500	19 700	13 200

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060460479
Diâmetro interior	16 mm
Diâmetro exterior	30 mm
Espessura	14 mm
Peso	107 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE