

Rolo de leva com eixo CFE20-VBUUR-IKO - CFE20-VBUUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe20-vbuur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)										
	Shield type		Sealed type		g	D	C	d _e							
27	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	505	52	24	27							
CFE 20 VBUUR															
Boundary dimensions mm															
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	G ₁	H	H ₁ (°)	f	Mounting dimension g	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M20 X 1.5	19.5	25.6	66.1	40.5	0.8	8	21	8	1	0.8	34	119	33 200	64 500	37 500

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060460622
Diâmetro interior	27 mm
Diâmetro exterior	52 mm
Espessura	24 mm
Peso	505 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE