

Rolo de leva com eixo CFE24-VBUUR-IKO - CFE24-VBUUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe24-vbuur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole

Outside diameter of eccentric roller mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
33			CFE 24	VBUUR			900	62	29	33

Boundary dimensions mm															
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	H	H ₁	Excentricity g	Mounting dimension f mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N		
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	12	1	0.8	40	215	46 600	92 000	52 000

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060460707
Diâmetro interior	33 mm
Diâmetro interior	1.299" inch
Diâmetro exterior	62 mm
Diâmetro exterior	2.441" inch
Espessura	29 mm
Espessura	1.142" inch
Peso	900 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE