


Rolo de leva com eixo CFE30-1-VBUUR-IKO - CFE30-1-VBUUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe30-1-vbuur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUUR

| Outside diameter of eccentric roller mm | Identification number | | | | | | Mass (Ref.) | | | |
|---|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|
| | Shield type | | | Sealed type | | | Ø | D | C | d _e |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | |
| 41 | CFE 30-1 VBUUR | | | | | | 2 190 | 85 | 35 | 41 |

| Boundary dimensions mm | | | | | | | | | | | | | | | |
|------------------------|----------------|-----------------------|-----------------------|----------------|----------------|---|------------------|------------------|-------------------------------|--------------------------------|-------------------------------------|---|------------------------------------|---------|--------|
| G | B ₃ | B ₁ max | B ₂ max | C ₁ | G ₁ | H | f _{max} | f _{min} | Mounting dimension f mm | Maximum splining torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N | | |
| M30×1.5 | 32.5 | 37 | 100 | 63 | 1 | 8 | 30.5 | 17 | 1 | 1.5 | 49 | 438 | 67 700 | 144 000 | 85 900 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3616060460820 |
| Diâmetro interior | 41 mm |
| Diâmetro exterior | 85 mm |
| Espessura | 35 mm |
| Peso | 2190 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE