

Rolo de leva com eixo CFE18-VUU-IKO - CFE18-VUU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe18-vuu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



CFE18-VUU

| Outside diameter of eccentric roller mm | Identification number | | | | Mass (Ref.) g | D | C | d _e |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|------------------|----|----|----------------|
| | Shield type | | Sealed type | | | | | |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | |
| 24 | | | | CFE 18 VUU | 285 | 40 | 20 | 24 |

| Boundary dimensions mm | | | | | | | | | | | | | | |
|------------------------|----------------|------------------|-------------------------------|----------------|----------------|----------------|----------------|--|-------------------|---------------------------------------|---------------------------------|-------------------------------------|---|------------------------------------|
| G | B ₃ | B _{max} | B ₁ _{max} | B ₂ | C ₁ | g ₁ | G ₁ | r ₁ ⁽¹⁾ _{min} | Excentricity E | Mounting dimension f Min. mm | Maximum operating torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
| M18 x 1.5 | 17.5 | 21.6 | 58.1 | 36.5 | 0.8 | 6 | 19 | 1 | 0.8 | 29 | 86.2 | 25 300 | 51 300 | 31 100 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3616060461162 |
| Diâmetro interior | 24 mm |
| Diâmetro exterior | 40 mm |
| Espessura | 20 mm |
| Peso | 285 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE