


Rolo de leva com eixo CFE20-V-IKO - CFE20-V-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfe20-v-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



| Outside diameter of eccentric roller mm | Identification number | | | | Mass (Ref.) g | D | C | d _e |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|------------------|----|----|----------------|
| | Shield type | | Sealed type | | | | | |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | |
| 27 | CFE 20 V | | | | 505 | 52 | 24 | 27 |

| Boundary dimensions mm | | | | | | | | | | | | | | |
|------------------------|----------------|------------------|-------------------------------|----------------|----------------|----------------|----------------|--|-------------------|---------------------------------------|---------------------------------|-------------------------------------|---|------------------------------------|
| G | B ₃ | B _{max} | B ₁ _{max} | B ₂ | C ₁ | g ₁ | G ₁ | r ₁ ^(*) _{min} | Eccentricity E | Mounting dimension f Min. mm | Maximum operating torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
| M20 × 1.5 | 19.5 | 25.6 | 66.1 | 40.5 | 0.8 | 8 | 21 | 1 | 0.8 | 34 | 119 | 33 200 | 64 500 | 37 500 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3616060461186 |
| Diâmetro interior | 27 mm |
| Diâmetro interior | 1.063" inch |
| Diâmetro exterior | 52 mm |
| Diâmetro exterior | 2.047" inch |
| Espessura | 24 mm |
| Espessura | 0.945" inch |
| Peso | 505 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE