

## Rolo de leva com eixo CR8-1-B-IKO - CR8-1-B-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr8-1-b-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



| Stud dia.<br>mm<br>(inch) | Identification number      |                                |                            |                                | Mass<br>(Ref.)<br>g | D              | C             | d <sub>1</sub> | G<br>UNF | G <sub>1</sub> |
|---------------------------|----------------------------|--------------------------------|----------------------------|--------------------------------|---------------------|----------------|---------------|----------------|----------|----------------|
|                           | Shield type                |                                | Sealed type                |                                |                     |                |               |                |          |                |
|                           | With covered<br>outer ring | With cylindrical<br>outer ring | With covered<br>outer ring | With cylindrical<br>outer ring |                     |                |               |                |          |                |
| 4.826                     | CR 8-1 B                   |                                |                            |                                | 10                  | 12.700 ( 1/2 ) | 9.525 ( 3/8 ) | 4.826          | No.10-32 | 6.350 ( 1/4 )  |

  

| Boundary dimensions mm/inch |                |                |                |                |                |               |                |  |   |  |  |
|-----------------------------|----------------|----------------|----------------|----------------|----------------|---------------|----------------|--|---|--|--|
| B<br>max                    | B <sub>2</sub> | B <sub>3</sub> | C <sub>1</sub> | E <sub>1</sub> | E <sub>2</sub> | H             | r              | Bearing<br>dimension<br>f<br>mm/<br>mm(inch) | Maximum<br>tightening<br>torque<br>C<br>N·m | Basic dynamic<br>load rating<br>C<br>N | Basic static<br>load rating<br>C <sub>0</sub><br>N |
| 10.9 ( 4/3 )                | 15.875 ( 5/8 ) | - (-)          | 0.794 ( 1/8 )  | - (-)          | - (-)          | 3.175 ( 1/4 ) | 0.207 ( 1/20 ) | 8.334 ( 1/3 )                                | 1.4   | 2 520                                  | 2 140  |

## CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | IKO           |
| Nº Ean13          | 3616060462312 |
| Diâmetro interior | 4.826 mm      |
| Diâmetro exterior | 12.7 mm       |
| Espessura         | 9.525 mm      |
| Peso              | 10 g          |
| Embalagem         | 1             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE