

## Rolo de leva com eixo CR16-BR-IKO - CR16-BR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr16-br-iko>

IKO  
**CAM FOLLOWERS**  
Inch Series Cam Followers With Cage/With Hexagon Hole

Stud dia. mm (inch)	Identification number				g	D	C	d <sub>1</sub>	G	G <sub>1</sub>	
	Shield type	Sealed type		Mass (Ref.)							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring					UNF		
11.112 ( $\frac{3}{8}$ )	CR 16 BR				73	25.400 (1)	15.875 (1/2)	11.112 (3/8)	$\frac{1}{8}$ -20	12.700 (1/2)	
Boundary dimensions mm(inch)											
B	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	E <sub>1</sub>	E <sub>2</sub>	H	r	Bearing dimension f Mm(inch)	Maximum spinning torque C N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
17.3 (3/8)	25.400 (1)	8.250 (1/2)	0.794 (1/32)	4.782 (1/8)	3.175 (1/8)	6.350 (1/4)	1.191 (1/32)	17.899 (1/2)	17.4	8 910	10 800

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060462473
Diâmetro interior	11.112 mm
Diâmetro exterior	25.4 mm
Espessura	15.875 mm
Peso	73 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE