


Rolo de leva com eixo CR16-BUUR-IKO - CR16-BUUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr16-buur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
11.112 ($\frac{3}{8}$)	CR 16 BUUR				73	25.400 (1)	15.875 ($\frac{5}{8}$)	11.112 ($\frac{3}{8}$)	$\frac{1}{2}$ -20	12.700 ($\frac{1}{2}$)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm(inch)	Maximum tightening torque C	Basic dynamic load rating N	Basic static load rating C ₀
17.3 (0.68)	25.400 (1)	8.350 ($\frac{1}{2}$)	0.794 ($\frac{1}{8}$)	4.782 ($\frac{3}{4}$)	3.175 ($\frac{1}{4}$)	6.350 ($\frac{1}{4}$)	1.191 ($\frac{1}{8}$)	17.859 ($\frac{5}{8}$)	17.4	8 910	10 800

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060462497
Diâmetro interior	11.112 mm
Diâmetro exterior	25.4 mm
Espessura	15.875 mm
Peso	73 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE