

Rolo de leva com eixo CR14-R-IKO - CR14-R-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr14-r-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Screwdriver Slot

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
9.525 ($\frac{3}{8}$)	CR 14 R				46	22.225 ($\frac{7}{8}$)	12.700 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	$\frac{1}{4}$ -24	9.525 ($\frac{3}{8}$)
Boundary dimensions mm(inch)										
B_{max}	B_2	B_3	C_1	E_1	E_2	F	Bearing dimension f mm($\frac{1}{32}$)	Maximum tightening torque C N·m	Basic dynamic load rating C_0 N	Basic static load rating C_0 N
14.2938	22.225 ($\frac{7}{8}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	2.381 ($\frac{3}{32}$)	0.794 ($\frac{1}{32}$)	15.081 ($\frac{1}{2}$)	10.8	4.790	9.810

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060462879
Diâmetro interior	9.525 mm
Diâmetro exterior	22.225 mm
Espessura	12.7 mm
Peso	46 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE