


## Rolo de leva com eixo CR16-IKO - CR16-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr16-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
11.112 ( $\frac{7}{16}$ )		CR 16			73	25.400 ( $\frac{1}{16}$ )	15.875 ( $\frac{5}{16}$ )	11.112 ( $\frac{7}{16}$ )	$\frac{1}{8}$ -20	12.700 ( $\frac{1}{2}$ )
Boundary dimensions mm(inch)										
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	S <sub>1</sub>	S <sub>2</sub>	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C <sub>0</sub>	Basic static load rating C <sub>0</sub>
17.3 0.68	25.400 ( $\frac{1}{16}$ )	6.350 ( $\frac{1}{4}$ )	0.794 ( $\frac{1}{16}$ )	4.702 ( $\frac{3}{16}$ )	3.175 ( $\frac{1}{8}$ )	1.191 ( $\frac{1}{16}$ )	17.859 ( $\frac{9}{16}$ )	17.4	8 910	10 800

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060462916
Diâmetro interior	11.112 mm
Diâmetro exterior	25.4 mm
Espessura	15.875 mm
Peso	73 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE