

Rolo de leva com eixo CR16-UUR-IKO - CR16-UUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr16-uur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
11.112 ($\frac{7}{16}$)			CR 16 / UUR		73	25.400	15.875	11.112	G ₁ -20	12.700
Boundary dimensions mm(inch)										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
17.3 0.68	25.400	6.350	0.794	4.762	3.175	1.191	17.859	17.4	8 910	10 800

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060462923
Diâmetro interior	11.112 mm
Diâmetro exterior	25.4 mm
Espessura	15.875 mm
Peso	73 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE