

## Rolo de leva com eixo CR32-R-IKO - CR32-R-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr32-r-iko>

IKO  
**CAM FOLLOWERS**  
Inch Series Cam Followers With Cage/With Screwdriver Slot

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
22.225 (7/8)	CR 32	R			615	50.800 (2)	31.750 (1 1/4)	22.225 (7/8)	7/8-14	25.400 (1)
Boundary dimensions mm(inch)										
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	δ <sub>1</sub>	δ <sub>2</sub>	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C <sub>0</sub>	Basic static load rating C <sub>0</sub>
33.5 (1.32)	50.800 (2)	12.700 (1/2)	0.794 (1/8)	4.762 (3/8)	4.762 (3/8)	1.588 (1/8)	37.306 (1 1/2)	192	32 500	69 900

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060463036
Diâmetro interior	22.225 mm
Diâmetro exterior	50.8 mm
Espessura	31.75 mm
Peso	615 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE