

Rolo de leva com eixo CR36-UUR-IKO - CR36-UUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr36-uur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
22.225 ($\frac{7}{8}$)	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring	750	57.150 ($2\frac{1}{4}$)	21.750 ($1\frac{1}{4}$)	22.225 ($\frac{7}{8}$)	7-14	25.400 (1)
Boundary dimensions mm(inch)										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
33.5 (1.32)	50.800 (2)	12.700 ($\frac{1}{2}$)	0.794 ($\frac{1}{8}$)	4.762 ($\frac{3}{8}$)	4.762 ($\frac{3}{8}$)	1.588 ($\frac{1}{8}$)	27.306 (1 $\frac{1}{8}$)	192	32 500	69 900

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060463050
Diâmetro interior	22.225 mm
Diâmetro exterior	57.15 mm
Espessura	31.75 mm
Peso	750 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE