


Rolo de leva com eixo CR8-V-IKO - CR8-V-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr8-v-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With coverd outer ring	With cylindrical outer ring	With shielded outer ring	With cylindrical outer ring						
4.826		CR 8 V			9	12.700	8.731	4.826	No.10-32	6.350

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B max	B ₂	B ₃	C ₁	g ₁	g ₂	r				
15.2(0.40)	12.7(0.50)	- (-)	0.794(0.031)	1.175(0.046)	- (-)	0.387(0.015)	0.324(0.013)	1.4	4 260	4 750

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060463098
Diâmetro interior	4.826 mm
Diâmetro exterior	12.7 mm
Espessura	8.731 mm
Peso	9 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE