


## Rolo de leva com eixo CR12-V-IKO - CR12-V-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr12-v-iko>

**IKO**  
**CAM FOLLOWERS**  
Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>
	Shield type With cover With cylindrical outer ring	Shield type With cylindrical outer ring	Sealed type With shield With cylindrical outer ring	Sealed type With cylindrical outer ring						
9.525 ( $\frac{3}{8}$ )		CR 12 V			36	19.050 ( $\frac{3}{4}$ )	12.700 ( $\frac{1}{2}$ )	9.525 ( $\frac{3}{8}$ )	$\frac{1}{4}$ -24	9.525 ( $\frac{3}{8}$ )
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>					g <sub>2</sub>	r
14.208	22.225 ( $\frac{7}{8}$ )	8.350 ( $\frac{1}{3}$ )	0.794 ( $\frac{1}{32}$ )	4.782 ( $\frac{1}{4}$ )	2.381 ( $\frac{1}{8}$ )	0.794 ( $\frac{1}{32}$ )	13.484 ( $\frac{1}{2}$ )	10.8	8 710	12 300

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060463401
Diâmetro interior	9.525 mm
Diâmetro exterior	19.05 mm
Espessura	12.7 mm
Peso	36 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE