


Rolo de leva com eixo CR18-VBUUR-IKO - CR18-VBUUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr18-vbuur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



CR18-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.)		d_1	G	G ₁		
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	g	D					
11.112 ($\frac{1}{2}$)			CR18	VBUUR	85	28.575 ($\frac{1}{2}$)	15.875 ($\frac{1}{2}$)	11.112 ($\frac{1}{2}$)	$\frac{1}{2}$ -20	12.700 ($\frac{1}{2}$)	
Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	
B max	B ₂	B ₃	C ₁	g ₁	g ₂	H					r
17.3 (0.68)	25.400 ($\frac{1}{2}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{32}$)	4.782 ($\frac{1}{8}$)	3.175 ($\frac{1}{8}$)	6.350 ($\frac{1}{4}$)	1.588 ($\frac{1}{16}$)	19.050 ($\frac{3}{4}$)	17.4	13 100	22 700

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060463685
Diâmetro interior	11.112 mm
Diâmetro exterior	28.575 mm
Espessura	15.875 mm
Peso	85 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE