


Rolo de leva com eixo CR26-VB-IKO - CR26-VB-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr26-vb-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR26-VB

| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G UNF | G ₁ | |
|------------------------------|-----------------------------------------|-----------------------------------------------|-----------------------------------------------|-----------------------------------------------|--------------------------|--------------------------|--------------------------|------------------------------------------------|----------------------------------------|----------------------------------------|----------------------------------------------------|
| | Shield type With cover outer ring | Shield type With cylindrical outer ring | Shield type With cylindrical outer ring | Shield type With cylindrical outer ring | | | | | | | |
| 15.875 ($\frac{5}{8}$) | | CR 26 VB | | | 265 | 41.275 ($\frac{1}{2}$) | 22.225 ($\frac{7}{8}$) | 15.875 ($\frac{5}{8}$) | $\frac{1}{4}$ -18 | 19.050 ($\frac{3}{4}$) | |
| Boundary dimensions mm(inch) | | | | | | | | | | | |
| B max | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | H | r | Mounting dimension f Min. mm(inch) | Maximum tightening torque N-m | Basic dynamic load rating C N | Basic static load rating C ₀ N |
| 23.8 (0.93) | 38.100 ($\frac{1}{2}$) | 9.525 ($\frac{3}{8}$) | 0.794 ($\frac{1}{16}$) | 4.762 ($\frac{3}{16}$) | 3.969 ($\frac{5}{32}$) | 7.938 ($\frac{1}{2}$) | 1.588 ($\frac{1}{16}$) | 26.195 ($\frac{1}{2}$) | 55.7 | 29 200 | 40 100 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3616060463999 |
| Diâmetro interior | 15.875 mm |
| Diâmetro exterior | 41.275 mm |
| Espessura | 22.225 mm |
| Peso | 265 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE