

## Rolo de leva com eixo CR26-VBUUR-IKO - CR26-VBUUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr26-vbuur-iko>

IKO  
**CAM FOLLOWERS**  
Inch Series Cam Followers **With Cage/With Screwdriver Slot**

CR26-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Screw type With screw outer ring	Screw type With cylindrical outer ring							
15.875 ( $\frac{5}{8}$ )			CR 26	VBUUR	265	41.275 ( $\frac{1}{2}$ )	22.225 ( $\frac{7}{8}$ )	15.875 ( $\frac{5}{8}$ )	$\frac{1}{4}$ -18	19.050 ( $\frac{3}{4}$ )	
Boundary dimensions mm(inch)											
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	H	r	Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
23.8 (0.93)	38.100 ( $\frac{1}{2}$ )	9.525 ( $\frac{3}{8}$ )	0.794 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{16}$ )	3.969 ( $\frac{1}{4}$ )	7.938 ( $\frac{1}{2}$ )	1.588 ( $\frac{1}{16}$ )	26.195 ( $\frac{1}{2}$ )	55.7	29 200	40 100

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060464002
Diâmetro interior	15.875 mm
Diâmetro exterior	41.275 mm
Espessura	22.225 mm
Peso	265 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE