

Rolo de leva com eixo CR26-VBUU-IKO - CR26-VBUU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr26-vbuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



CR26-VBUU

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Screw slot type With cylindrical outer ring	Screw slot type With cylindrical outer ring							
15.875 ($\frac{5}{8}$)			CR 26	VBUU	265	41.275 ($\frac{1}{2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	$\frac{1}{4}$ -18	19.050 ($\frac{3}{4}$)	
Boundary dimensions mm(inch)											
B max	B ₂	B ₃	C ₁	g ₁	g ₂	H	r	Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
23.8 (0.93)	38.100 (1 $\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	3.969 ($\frac{1}{8}$)	7.938 ($\frac{1}{2}$)	1.588 ($\frac{1}{16}$)	26.195 (1 $\frac{1}{8}$)	55.7	29 200	40 100

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060464019
Diâmetro interior	15.875 mm
Diâmetro exterior	41.275 mm
Espessura	22.225 mm
Peso	265 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE