

Rolo de leva com eixo CR30-V-IKO - CR30-V-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr30-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type With cover With cylindrical outer ring		Sealed type With shield With cylindrical outer ring		ϕ	D	C	d_1	G UNF	G_1
19.050 ($\frac{3}{4}$)	CR 30 V				418	47.625 ($\frac{1}{2}$)	25.400 (1)	19.050 ($\frac{3}{4}$)	$\frac{1}{8}$ -16	22.225 ($\frac{7}{8}$)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N		
B max	B_2	B_3	C_1	g_1					g_2	r
25.8100	44.650 ($\frac{1}{2}$)	11.112 ($\frac{1}{2}$)	0.794 ($\frac{1}{4}$)	4.762 ($\frac{1}{4}$)	3.969 ($\frac{1}{4}$)	1.588 ($\frac{1}{4}$)	32.543 ($\frac{1}{2}$)	100	35 300	55 800

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060464101
Diâmetro interior	19.05 mm
Diâmetro exterior	47.625 mm
Espessura	25.4 mm
Peso	418 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE