


Rolo de leva com eixo CR32-VB-IKO - CR32-VB-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cr32-vb-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
22.225 ($\frac{7}{8}$)		CR 32 VB			627	50.800 (2)	31.750 (1) ($\frac{5}{8}$)	22.225 ($\frac{7}{8}$)	$\frac{1}{4}$ -14	25.400 (1)	
Boundary dimensions mm(inch)											
B max	B ₂	B ₃	C ₁	g ₁	g ₂	H	r	Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
33.5 (1.32)	50.800 (2)	12.700 ($\frac{1}{2}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	4.762 ($\frac{3}{16}$)	11.112 ($\frac{7}{16}$)	1.588 ($\frac{1}{16}$)	37.305 (1) ($\frac{1}{2}$)	162	45 700	80 600

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060464224
Diâmetro interior	22.225 mm
Diâmetro exterior	50.8 mm
Espessura	31.75 mm
Peso	627 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE