

Rolo de leva com eixo CRH44-V-IKO - CRH44-V-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/crh44-v-iko>

IKO
CAM FOLLOWERS
Inch Series Heavy Duty Cam Followers Full Complement Type/With Screwdriver Slot

CRH44-V

| Stud dia. mm (inch) | Identification number | | Mass (Ref.) g | D | C | d ₁ | G LINE | G ₁ | B max |
|---------------------------|-----------------------|-------------|---------------------|----------------|----------------|----------------|---------------------|----------------|--------------|
| | Shield type | Sealed type | | | | | | | |
| 31.750 (1.25) | CRH 44 | V | 1 460 | 69.850 ± 0.025 | 38.100 ± 0.025 | 31.750 ± 0.025 | 17 _C -12 | 28.575 ± 0.025 | 40.0 ± 0.151 |

| Boundary dimensions | | | | | | | Mounting dimension f Min. mm(inch) | Maximum operating temp N-m | Basic dynamic load rating C | Basic static load rating C ₀ |
|---------------------|----------------|----------------|----------------|----------------|---------------|----------------|---|-------------------------------------|-----------------------------------|---|
| B ₂ | B ₃ | C ₁ | S ₁ | S ₂ | r | mm(inch) | | | | |
| 57.150 ± 0.025 | 14.288 ± 0.025 | 1.588 ± 0.025 | 4.782 ± 0.025 | 3.175 ± 0.025 | 2.381 ± 0.025 | 40.878 ± 0.025 | 500 | 61 400 | 116 000 | |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3616060464804 |
| Diâmetro interior | 31.75 mm |
| Diâmetro exterior | 69.85 mm |
| Espessura | 38.1 mm |
| Peso | 1460 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE