

## Rolamento de rolos NN3022K-JTEKT - NN3022K-KOYO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nn3022k-koyo>

### Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
d	D	B	r min.	F <sub>w</sub>	E <sub>0</sub>	C <sub>10</sub>	C <sub>02</sub>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
110	170	45	2	—	155	221	361	3 500	4 200	—	—

  

Mounting dimensions (mm)		Cylindrical bore		Tapered bore		Mass (kg)	
d <sub>a</sub> min.	d <sub>a</sub> max.	D <sub>a</sub> min.	D <sub>a</sub> max.	r <sub>s</sub> min.	r <sub>s</sub> max.	Cylindrical bore	Tapered bore
119	—	—	161	157	2	3.55	3.56

## CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952473062
Diâmetro interior	110 mm
Diâmetro exterior	170 mm
Espessura	45 mm
Peso	3560 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE