


Arruela de batente GS130170-IKO - GS130170-IKO

<https://www.123rolamento.pt/accessorio/arruela/arruela-batente/gs130170-iko>

IKO
THRUST BEARINGS
Thrust Needle Roller Bearings



Shaft dia. mm	Identification number							
	Thrust needle roller bearing	Mass (Ref.) g	Thrust washers	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
130	NTB 130170	225	—	—	WS 130170	GS 130170	660	

Boundary dimensions mm							Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	
d	D	D _w	s	B	r _s min ⁽¹⁾	C _i				
130	170	5	—	9	1	137	165	120 000	839 000	1 700

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060465863
Diâmetro interior	130 mm
Diâmetro exterior	170 mm
Espessura	9 mm
Material	AÇO
Peso	660 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE