

Batente de agulhas AZ254211-IKO - AZ254211-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/batente-agulhas/az254211-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings

Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
25	AZ 254211	70	AZK 25425	28	WS 2542	GS 2542	21	

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d _s Min.	d _s Max.	N	N	rpm
25	42	11	25.05	41.6	5	3	0.6	28	39	39	28	22 700	60 700	9 000

Notes: ^(*) Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060465900
Diâmetro interior	25 mm
Diâmetro exterior	42 mm
Espessura	11 mm
Peso	70 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE