


Arruela de batente GS90160-IKO - GS90160-IKO

<https://www.123rolamento.pt/accessorio/arruela/arruela-batente/g90160-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
90	AZ 9016026	2 710	AZK 9016010	1 000	WS 90160	GS 90160	855

Boundary dimensions mm										Standard mounting dimensions mm	Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂					d _s Min.
90	160	26	90.05	159.5	10	8	1.5	109	149	149	110	189 000	871 000	2 500

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952488349
Diâmetro interior	90 mm
Diâmetro exterior	160 mm
Espessura	8 mm
Material	AÇO
Peso	855 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE