

## Arruela de batente GS150250-IKO - GS150250-IKO

<https://www.123rolamento.pt/accessorio/arruela/arruela-batente/g150250-iko>

**IKO**  
**THRUST BEARINGS**  
Thrust Roller Bearings

| Shaft dia. mm | Identification number |               |                       |               |            |            |               |
|---------------|-----------------------|---------------|-----------------------|---------------|------------|------------|---------------|
|               | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g |
| 150           | AZ 15025039           | 9 140         | AZK 15025015          | 3 280         | WS 150250  | GS 150250  | 2 940         |

  

| Boundary dimensions mm |     |    |                |                |                |    |                    |                |                | Standard mounting dimensions mm |                     | Basic dynamic load rating C | Basic static load rating C <sub>0</sub> | Allowable rotational speed <sup>(*)</sup> |
|------------------------|-----|----|----------------|----------------|----------------|----|--------------------|----------------|----------------|---------------------------------|---------------------|-----------------------------|---|---|
| d                      | D   | T  | d <sub>c</sub> | D <sub>c</sub> | D <sub>w</sub> | B  | r <sub>s</sub> (1) | C <sub>1</sub> | C <sub>2</sub> | d <sub>s</sub> Min.             | D <sub>s</sub> Max. | N                           | N                                       | rpm                                       |
| 150                    | 250 | 39 | 150.1          | 249            | 15             | 12 | 2.1                | 171            | 237            | 236                             | 172                 | 459 000                     | 2 380 000                               | 1 500                                     |

Notes: (\*) Minimum allowable value of chamfer dimension r  
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

## CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | IKO           |
| Nº Ean13          | 3616060467201 |
| Diâmetro interior | 150 mm        |
| Diâmetro exterior | 250 mm        |
| Espessura         | 12 mm         |
| Material          | AÇO           |
| Peso              | 2940 g        |
| Embalagem         | 1             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE