


Arruela de batente WS160200-IKO - WS160200-IKO

<https://www.123rolamento.pt/accessorio/arruela/arruela-batente/ws160200-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings



Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
160	AZ 16020031	2 710	AZK 16020012	1 030	WS 160200	GS 160200	840	

Boundary dimensions mm										Standard mounting dimensions mm	Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂					d ₄ Min.
160	200	31	160.1	199.5	12	9.5	1	170	194	193	170	189 000	895 000	1 700

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060467218
Diâmetro interior	160 mm
Diâmetro exterior	200 mm
Espessura	9.5 mm
Material	AÇO
Peso	840 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE