


## Arruela de batente GS240380-IKO - GS240380-IKO

<https://www.123rolamento.pt/accessorio/arruela/arruela-batente/gs240380-iko>

**IKO**  
**THRUST BEARINGS**  
Thrust Roller Bearings



| Shaft dia. mm | Identification number |               |                       |               |            |            |               |
|---------------|-----------------------|---------------|-----------------------|---------------|------------|------------|---------------|
|               | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g |
| 240           | AZ 24038052           | 26 500        | AZK 24038020          | 9 440         | WS 240380  | GS 240380  | 8 530         |

| Boundary dimensions mm |     |    |                |                |                |    |                    |                |                | Standard mounting dimensions mm |                     | Basic dynamic load rating C | Basic static load rating C <sub>0</sub> | Allowable rotational speed <sup>(2)</sup> |
|------------------------|-----|----|----------------|----------------|----------------|----|--------------------|----------------|----------------|---------------------------------|---------------------|-----------------------------|---|---|
| d                      | D   | T  | d <sub>c</sub> | D <sub>c</sub> | D <sub>w</sub> | B  | r <sub>s</sub> (1) | C <sub>1</sub> | C <sub>2</sub> | d <sub>s</sub> Min.             | D <sub>s</sub> Max. | N                           | N                                       | rpm                                       |
| 240                    | 380 | 52 | 240.15         | 378            | 20             | 16 | 4                  | 266            | 363            | 362                             | 267                 | 977 000                     | 5 910 000                               | 1 000                                     |

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

### CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | IKO           |
| Nº Ean13          | 3616060467485 |
| Diâmetro interior | 240 mm        |
| Diâmetro exterior | 380 mm        |
| Espessura         | 16 mm         |
| Material          | -             |
| Peso              | 8530 g        |
| Embalagem         | -             |
| Padrão            | -             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE