

Arruela de batente GS260420-IKO - GS260420-IKO

<https://www.123rolamento.pt/accessorio/arruela/arruela-batente/g260420-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings

Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
260	AZ 26042080	51 600	AZK 26042030	18 200	WS 260420	GS 260420	18 700	

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
260	420	80	260.15	418	30	25	5	289	402	400	291	1 430 000	7 490 000	900

Notes: ^(*) Minimum allowable value of chamfer dimension r
⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060467522
Diâmetro interior	260 mm
Diâmetro exterior	420 mm
Espessura	25 mm
Material	AÇO
Peso	16700 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE