

Rótula SI SI8-T-K-DURBAL - SI8-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/si8-t-k-durbal>


SI8-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI	B T/K	8	M 8	12	9,00	24	12,5	16
type	measurement [mm]			load rating	weight			
	l ₁ min	W	h	C ₁ [N]	[kg]			
SI / SIL	B T/K	16	14	36	14	12,9	0,047	

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952489148
Diâmetro interior	8 mm
Diâmetro exterior	24 mm
Espessura	12 mm
Tipo	SI
Peso	47 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE