

Rótula SI

SIL8-T-K-DURBAL - DSIL8-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/dsil8-t-k-durbal>


SIL8-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄	W
SIL 8 T/K		8	M 8	12	9,00	24	12,5	16	

type	measurement [mm]			d ₁	load rating C ₁₀ [N]	weight [kg]
	l ₁ min	W	h			
SI / SIL 8 T/K	16	14	36	14	12,9	0,047

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952489155
Diâmetro interior	8 mm
Diâmetro exterior	24 mm
Espessura	12 mm
Tipo	SI
Peso	47 g
Linha	Rosca esquerda
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE