

Rótula SI

SI12-T-K-DURBAL - SI12-T-K-DURBAL

https://www.123rolamento.pt/rolamento-mancal/rotula/si/si12-t-k-durbal

SI12-T-K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

female thread: maintenance free, according to DIN ISO 12240-4, series K

Red end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 12 TIK		12	M 12	16	12,00	32	17,5	22

type	measurement [mm]			load rating C ₀ [N]	weight [g]	
	l ₃ min	W	h			
SI / SI12 TIK	22	19	50	13	24,0	0,100

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952489285
Diâmetro interior	12 mm
Diâmetro exterior	32 mm
Espessura	16 mm
Tipo	-
Peso	100 g
Linha	-
Lubrificação	-
Embalagem	-

contato@123rolamento.pt
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE