

Rótula SI SI18-T-K-DURBAL - SI18-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/si18-t-k-durbal>


SI18-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

| order number | | measurement [mm] | | | | | | |
|-------------------|------------------|------------------|------------|----|----------------|----------------|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ | d ₃ | d ₄ |
| SI 18 TIK | | 18 | M 18 x 1,5 | 23 | 16,50 | 44 | 25,0 | 31 |

| type | measurement [mm] | | | load rating C ₀ [N] | weight [kg] |
|---------------|--------------------|----|----|--------------------------------------|----------------|
| | l ₁ min | W | h | | |
| SI / SI18 TIK | 32 | 27 | 71 | 15 | 47,5 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | DURBAL |
| Nº Ean13 | 3663952489520 |
| Diâmetro interior | 18 mm |
| Diâmetro exterior | 44 mm |
| Espessura | 23 mm |
| Tipo | SI |
| Peso | 320 g |
| Linha | Rosca direita |
| Lubrificação | sem |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE