

Rótula SI SI20-T-K-DURBAL - SI20-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/si20-t-k-durbal>


SI20-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 20 TIK		20	M 20 x 1,5	25	18,00	50	27,5	34

type	measurement [mm]			load rating C ₀ [N]	weight [kg]
	l ₁ min	W	h		
SI / SIH 20 TIK	33	30	77	14	0,420

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952489537
Diâmetro interior	20 mm
Diâmetro exterior	50 mm
Espessura	25 mm
Tipo	SI
Peso	420 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE