

Rótula SI SI22-T-K-DURBAL - SI22-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/si22-t-k-durbal>


SI22-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 22 TK		22	M 22 x 1,5	28	20,00	54	30,0	38

type	measurement [mm]			d ₁	load rating C ₀ [N]	weight [kg]
	l ₁ min	W	h			
SI / SIH 22 TK	37	32	84	15	68,0	0,540

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952489605
Diâmetro interior	22 mm
Diâmetro exterior	54 mm
Espessura	28 mm
Tipo	SI
Peso	540 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE