

Rótula SI SI28-T-K-DURBAL - SI28-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/si28-t-k-durbal>


SI28-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 28 TIK		28	M 27 x 2	35	24,00	66	37,0	46

type	measurement [mm]			load rating C ₁₀ [N]	weight [kg]
	l ₃ min	W	h		
SI / SI1 28 TIK	51	41	103	15	107,0

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
N° Ean13	3663952489681
Diâmetro interior	28 mm
Diâmetro interior	1.102" inch
Diâmetro exterior	66 mm
Diâmetro exterior	2.598" inch
Espessura	35 mm
Espessura	1.378" inch
Tipo	SI
Peso	820 g
Linha	Rosca direita
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE