

Rótula SI

SIL30-T-K-DURBAL - SIL30-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/sil30-t-k-durbal>


SIL30-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIL 30 T/K			30	M 30 x 2	37	25,00	70	40,0	50

type	measurement (mm)				load rating C ₀ (N)	weight (kg)
	l ₁ min	W	h	d ₁		
SI / SIL 30 T/K	51	41	110	17	114,0	1,100

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952489728
Diâmetro interior	30 mm
Diâmetro interior	1.181" inch
Diâmetro exterior	70 mm
Diâmetro exterior	2.756" inch
Espessura	37 mm
Espessura	1.457" inch
Tipo	SI
Peso	1100 g
Linha	Rosca esquerda
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE