

Rótula SI

SIL40-T-K-DURBAL - SIL40-T-K-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/sil40-t-k-durbal>


SIL40-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SIL 40 T/K			40	M 42 x 2	49	33,00	91	53,0	65

type	measurement (mm)			load rating	weight
	l ₃ min	W	h	C ₃ (kN)	(kg)
SI / SIL 40 T/K	60	55	142	17	2,400

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952489810
Diâmetro interior	40 mm
Diâmetro exterior	91 mm
Espessura	49 mm
Tipo	SI
Peso	2400 g
Linha	Rosca esquerda
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE